



MI-COMP-TI 3,6kV 1150A 40kA/1s MANUAL
with earthing device 10kA/1s

MAIN FEATURES

The disconnecter – earthswitch combination type MI-COMP-TI has following features:

- Disconnector with 2 positions: Closed – open
- Earthswitch with 2 positions: Closed - open
- Earthswitch mechanically interlocked: earthing only possible with disconnector in open position
- I_k value of earthing device is not always the same as main isolator
- Standard execution: 3pole. Also available as 1p, 2p, 4p or 5p execution.
- On demand : mounting of switch possible in each position
- On demand : High Endurance (=HE) execution (> 50.000 C-O)

ACCESSORIES (See also BR080 for more information)

- Beside standard execution, other types of auxiliary contacts available:
 - Heavy DC-currents
 - Very low currents (e.g. PLC-applications)
 - Positively driven contacts (IEC 60947-5-1)
 - IP67 execution
- Electro-mechanical interlock (100% ED) standard in several supply voltages:
 - 24, 110-125, 205-220 VDC
 - 230 VAC
 - Standard execution = interlocking without voltage supply
- Standard motor drives available, type D or M in several supply voltages:
 - 24, 110, 125, 220 VDC
 - 230, 3x400 VAC
 - Control system standard included and mounted on the disconnector
 - Manual emergency lever included
- Shaft extensions and removable operating levers for manual disconnectors
- Key or padlock interlock