

Compact isolator for indoor use

Conform IEC 62271-102


EME type MI-UI-ECO

*U_r: 7,2 - 36 kV


*I_r: 400 - 630 A

*I_k: 12,5 - 25 kA/1s

* Other values available on demand!



MI-UI-ECO 36kV 630A



MI-UI-ECO 12kV 630A

MAIN FEATURES

The one pole disconnecter MI-UI-ECO has following features:

- Disconnecter with 2 positions: Closed - open
- Mechanical endurance class M0; 1000 C-O (close-open cycles)
- Low-cost version of the standard MI-UI with the same active parts, but cheaper frame and shaft parts
- On demand : mounting of switch possible in each position

ACCESSORIES (See also BR080 for more information)

- Beside standard execution, other types of auxiliary contacts available:
 - Heavy DC-currents
 - Very low currents (e.g. PLC-applications)
- Electro-mechanical interlock (100% ED) standard in several supply voltages:
 - 24, 110-125, 205-220 VDC
 - 230 VAC
 - Standard execution = interlocking without voltage supply
- Shaft extensions and removable operating levers for manual disconnectors
- Key or padlock interlock
- Insulators with higher creepage distance



Electro Mechanic Equipment nv-sa
Zuurbemde 51
3380 Glabbeek (Belgium)

www.eme.be thv@eme.be

+32 (0)16 77 23 00 +32 (0)16 77 89 03
BTW-VAT-TVA : BE 0415.742.790